



# ACC Superplasticizer Polycarb—JNX

## Viscosity-reducing polycarboxylate superplasticizer

### Description

JNX is a new type of concrete admixture produced by high technology synthesis method through high polymer structure design. It can effectively adjust the viscosity of high grade concrete, and has the effect of low air-entraining and large strength increase.

### Features

- Light brown or colorless liquid.
- Has good stability and no precipitation at low temperature.
- Green environmental protection, non-toxic and harmless, conducive to the preparation of green concrete.
- Improve the adaptability of polycarb to cement, Fly Ash and GGBFS.
- Improve the adaptability of polycarb to sand and mud content.
- Improve the adaptability of polycarb to temperature and climate.
- Improve the viscosity of high grade concrete, and the strength of high grade concrete.



### Specifications

Chemical and Physical Properties	Value
Solid Content	40 ± 1 %
pH	6 ± 2
Bulk Density	1.080 ± 0.02 g/cm <sup>3</sup> (25°C)

### Application

JNX can be applied in the production of ready-mixed pump-delivery commodity concrete and in the preparation of high-fluidity concrete. Meanwhile, it can be widely applied to cast-in-site concrete, premixed concrete, prestressed concrete and other concrete constructions like industrial and civil buildings.

### Usage

- The recommended dosage is 20-80% when mix with conventional superplasticizer.
- Users in the first use of this product or temporary replacement of cement varieties, please according to the construction requirements, conditions, reference to this manual, do the necessary test for the amount of mixing and methods, in order to obtain the best technical, economic benefits.
- The product can not be mixed with Sodium Naphthalene Formaldehyde, so as not to affect the performance.

# Packaging and Storage

- 200kg or 1000kg per plastic drum, or as per customer's special request.
- The product is non-toxic and non-flammable.
- This product should be stored in a cool place, avoid contact with steel products for a long time, should be covered for storage, should avoid the sun, rain and freezing, the storage temperature should be between 0-40°C, storage below 0°C will have the phenomenon of freezing, if found frozen can be heated until it melts and stir again evenly before use.

The shelf life of this product is six months. If expired, the product shall be used after passing the inspection of

# Health and Safety

Wear suitable protective equipment to prevent contact with eyes, skin and clothing. Keep and store in a cool & dry place and keep away from direct heat and light. For further information please follow the Material Safety Data Sheet.

# Limited Warranty Notice

While ACC guarantees our products against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with ACC that the product is suitable for the intended use. Technical characteristics are listed for guidance only.

# Technical Services

We have a perfect after-sales service mechanism, provide technical advice for users, product performance can reach the best user satisfaction effect.



---

## Xiamen All Carbon Corporation

TEL: +86 592 2278129

FAX: +86 592 2278123

E-MAIL: info@allcarbon.com.cn

www.allcarbon.com.cn

Add: Unit F-G, 10/F, Zhenhaoge Building, Guomao Golden Coast,  
No.99 Lujiang Road, Xiamen, China, 361001

